



MAZZONETTO Spa
Via A. Ceccon, 10 - 35010 Loreggia (PD)
t. +39 049 9322611 - f. +39 049 9322650
mazzonetto@mazzonettometalli.it
www.mazzonettometalli.it



GALVANIZED PREPAINTED STEEL ANTISLIP strip **Quality: two-surfaces paint - Micron 25/17**

Normativa di Riferimento:	
UNI EN 10346; UNI EN 10169-1; UNI EN 13523 ; UNI EN 10143	
Technical features:	
Base metal	DX52D + Z
Nature of coating	Zinc
Quantity of coating	100 g/ m ²
Protection film thickness	Front side:25µm (+/- 5 µm): primer+polyester coating Back side:17µm : primer+polyester coating
Standard colors	Testa di moro - Ral 7037
Reaction to fire classification	Class A1
Mechanical properties:	
Tensile strength	From 270 to 500 MPa
Elongation	22% min.
Cracking resistance in bending (bend testing)	≤ 3,0 T
Coating adhesion	≤ 2,0 T
Pencil hardness	From HB to H
Corrosion resistance	- salt spray test: 240 h - Corrosion resistance class:RC2
UV rays resistance	- QUV test 2000 h - Class of UV resistance: RUV2
Dimensional characteristics:	
Standard thicknesses	0.55 mm
Standard width	mm 1000 - 1250 or compatible widths
Coil weight	From kg 250 to kg 5000
Use:	
Civil and industrial building industry and panels	