



**MAZZONETTO Spa**  
Via A. Ceccon, 10 - 35010 Loreggia (PD)  
t. +39 049 9322611 - f. +39 049 9322650  
mazzonetto@mazzonettometalli.it  
www.mazzonettometalli.it



## NATURAL TITANIUM ZINC strips

<b>Technical features:</b>	
Standard	UNI EN 988
Metal base	Zinco 99.99 %
Specific weight	7.2 Kg/dm <sup>3</sup>
Melting point	420°C
Longitudinal thermal expansion coefficient at (20°C-100°C)	0.022 mm/m°C
Erichsen drawability	7 – 9 mm
<b>Mechanical features:</b>	
Tensile strength	150 MPa min.
Elongation	40 – 55%
Hardness, min.	45 HV
<b>Chemical composition:</b>	
Zinc (Zn)	99.99 %
Titanium (Ti)	0.06 – 0.2 %
Copper (Cu)	0.08 – 1.00%
<b>Dimensional characteristics:</b>	
Standard thicknesses	0.65 – 0.70 – 0.80 mm
Dimensional tolerance	UNI EN 988
Standard width	900 - 1000 mm All widths on request
Coil weight	From 500 to 5000 kg
<b>Use:</b>	
Civil and industrial building industry and panels	